


COMPLETE INSTRUCTIONS FOR THE


LEE AUTO-PRIME II

NOT FOR USE ON PRESSES WITH AN INCLINED RAM

- 1** Assemble the lock ring and "O" ring onto the die and screw the assembly into your press.
- 2** Slip the spring over the proper punch (large or small) and drop it into the tool with the **large end down**.
- 3** Insert the large or small primer trough into the tool. (See letter on side).
- 4** Install the proper shell holder into the Auto-Prime II.



- 5** Snap the push rod into the ram where the shell holder normally fits.
- 6** Place no more than 100 CCI or Winchester brand primers in the tray. (Use of any other brand exposes the operator to unnecessary risks). With cover off, shake side to side to turn all primers right side up.



- 7** With cover on, use a pencil to hold the primers in the tray while assembling it to the priming tool.



- 8** Shake the unit side-to-side to fill the primer trough. **Do not point the unit at your face. Wear safety glasses.**

90107

LEE
Auto-Prime II

LEE PRECISION, INC.



7

WARNING

Primers are dangerous and it should be anticipated that the primers in the tray could explode through accident, misuse or spontaneously.

Should an explosion occur, our tests have demonstrated that safety glasses will normally prevent serious injury to the user if CCI or WINCHESTER primers are used, because the explosion is minimal. Other primers, however, can explode with sufficient force to seriously injure the user, or persons nearby. We do not take any position with respect to the quality or performance of primers available on the market. However, **only** those primers manufactured by CCI or WINCHESTER are recommended for use in the Lee AUTO-PRIME II, and when loading those primers, safety glasses should always be used. **No other primers** should be used with the Lee AUTO-PRIME II.

